



NOTE:

1. SPEED BUMP SHALL BE CONSTRUCTED OF HOT MIX ASPHALT CLASS 3/8" PG 58H-22 0.3 TO 3.0 ESAL MIX DESIGN UNLESS OTHERWISE SPECIFIED.

SIGNS:

- ① INSTALL MUTCD STANDARD W17-1 ("SPEED BUMP") SIGN 150' (POSTED SPEED=25MPH) OR 175' (POSTED SPEED=30MPH) AHEAD OF RAISED CROSSWALK AT BEGINNING OF A SERIES OF HUMPS OR AS NECESSARY. SEE **SIGN MOUNTING DETAILS T29-02 AND T29-03.**
- ② IN PLACING SIGNS AT MULTIPLE SPEED BUMPS ALONG A ROADWAY, HAVE THE SIGNS AT THE BEGINNING OF THE INSTALLATION WITH SUPPLEMENTAL SIGN "W16-4" DESIGNATING HOW MANY BLOCK, NOT AT EACH RAISED CROSSWALK.

I:\CITYAPPS\AUTOCAD\STD_DETAILS\DRAWING_FILES\T02-22

REV NO.	DATE	BY	APPR	PUBLIC WORKS - STREETS AND TRANSPORTATION
1	2/07	RAW	MHA	
2	8/08	RAW	MHA	
3	7/14	RAW	MHA	
4	1/15	RAW	MHA	
5	7/19	RAW	MHA	
6	9/21	RAW	MHA	

APPROVED BY: *M.H. Pedulla*
ENGINEER MANAGER
APPROVED DATE: 9/1/2021



SPEED BUMP	STANDARD PLAN NUMBER T02-22
------------	--------------------------------