



- ① PREFERRED TWO-WAY DRIVE OPPOSITE MEDIAN OPENINGS.
- ② PREFERRED TWO WAY DRIVE FOR INDUSTRIAL USES ON HIGH VOLUME STREETS.
- ③ RAISED MEDIAN SET BACK FROM STREET TO ALLOW PEDESTRIAN TRAFFIC.

NOTES:

1. MINIMUM DRIVE LENGTH IS 20 FEET, MEASURED FROM THE BACK OF SIDEWALK TO THE ENTRANCE OF THE OFF STREET PARKING AREA.
2. DIMENSIONS MAY VARY WITH ANALYSIS OF THE TURNING MOVEMENTS OF THE TYPICAL VEHICLE.

I:\CITYPPS\AUTOCAD\STD_DETAILS\DRAWING_FILES\T04-09

REV. NO.	DATE	BY	APPR	PUBLIC WORKS - STREETS AND TRANSPORTATION
1	3/06	RAW	MHA	
2	2/07	RAW	MHA	
3	8/08	RAW	MHA	
4	7/14	RAW	MHA	
5	3/17	RAW	MHA	
6	9/21	RAW	MHA	

APPROVED BY: *M.H. Sedalla*
ENGINEER MANAGER
APPROVED DATE: 9/1/2021



COMMERCIAL/HIGH VOLUME TWO-WAY DRIVEWAYS

STANDARD PLAN NUMBER T04-09