


- NOTES:**
1. ALL CONCRETE POST BASES SHALL BE 10" (IN) MINIMUM DIAMETER.
 2. ALONG THE TOP AND BOTTOM, USING HOG RINGS, FASTEN THE CHAIN LINK FENCE FABRIC TO THE TENSION WIRE WITHIN THE LIMITS OF THE FIRST FULL FABRIC WEAVE.
 3. DETAILS ARE ILLUSTRATIVE AND SHALL NOT LIMIT HARDWARE DESIGN OR POST SELECTION OF ANY PARTICULAR FENCE TYPE.
 4. FENCING SHALL BE USED FOR SECURITY AND BOUNDARY DELINEATION ONLY.
 5. ALL FENCE MATERIAL SHALL BE BLACK VINYL COATED.
 6. SEE CHAIN LINK FENCE BLOW-UP DETAILS ON T07-07B.
- 15 TWISTED KNUCKLED SELVAGE (TYP.)
 - 16 TENSION WIRE ALONG BOTTOM OF FENCE (TYPE 3 FENCE ONLY) (TYP.)
 - 17 HOG RINGS (TYPE 3 FENCE ONLY) SPACED AT 24" (IN.) MAX. (TYP.)
 - 18 POST BASE DEPTH:
TYPE 3 FENCE = 3'-0" (TYP.)
TYPE 4 FENCE = 2'-0" (TYP.)
 - 19 CONCRETE DEPTH BELOW POST:
TYPE 3 FENCE = 0'-6" (TYP.)
TYPE 4 FENCE = 0'-2" (TYP.)
 - 20 LINE POST DEPTH:
TYPE 3 FENCE = 2'-6" (TYP.)
TYPE 4 FENCE = 1'-10" (TYP.)
 - 21 FABRIC HEIGHT:
TYPE 3 FENCE = 6'-0" (TYP.)
TYPE 4 FENCE = 4'-0" (TYP.)

POST AND RAIL SPECIFICATIONS	
POST	PIPE
	NOM. SIZE (SCH. 40) I.D.
END, CORNER, OR PULL POST	2 1/2" DIAM.
LINE OR BRACE POST	2" DIAM.
TOP RAIL POST	1 1/4" DIAM.

REV	NO.	DATE	BY	APPROVED
1	3/16	RAW	MHA	
2	9/21	RAW	MHA	

PUBLIC WORKS - STREETS AND TRANSPORTATION

APPROVED BY: *M. H. Schell*
ENGINEER MANAGER 9/1/2021



CHAIN LINK FENCE
TYPES 3 AN 4

STANDARD PLAN NUMBER
T07-07A