



- ① CONCRETE POST BASE DEPTH (TYP.):
TYPE 3 FENCE = 3'-0"
TYPE 4 FENCE = 2'-0"
 - ② GATE POST (TYP.) ~ 3 1/2" (IN.) DIAM. (NOM. SCH. 40)
 - ③ TOP HINGE ~ 90° SWING (TYP.)
 - ④ BOTTOM HINGE ~ 90° SWING (TYP.)
 - ⑤ TRUSS ROD (TYP.)
 - ⑥ TIE WIRES (TYP.) ~ SPACED AT 14" (IN.) MAX.
 - ⑦ TOP RAIL (TYP.)
 - ⑧ HOG RINGS ~ SPACED AT 24" (IN.) MAX. (TYP.)
 - ⑨ TENSION WIRES (TYP.)
 - ⑩ FABRIC BAND (TYP.)
 - ⑪ STRETCHER BAR (TYP.)
 - ⑫ PULL POST
- NOTES:**
- ⑬ CHAIN LINK FENCE FABRIC (TYP.)
 - ⑭ MATCH FENCE SELVAGE (TYP.)
 - ⑮ TENSION WIRE ALONG BOTTOM OF FENCE (TYPE 3 FENCE ONLY) (TYP.)
 - ⑯ TENSION WIRE FOR GATE POST ~ REQUIRED ONLY ON HINGE SIDE
- 1. MATERIALS SHALL MEET THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS 9-16.
 - 2. ALL FENCE MATERIAL SHALL BE BLACK VINYL COATED.

REV. NO.	DATE	BY	APPROVED
1	3/16	RAW	MHA
2	9/21	RAW	MHA

PUBLIC WORKS – STREETS AND TRANSPORTATION

APPROVED BY: *M. H. Anderson*
ENGINEER MANAGER 9/1/2021



CHAIN LINK SINGLE GATE
TYPES 3 AND 4

STANDARD PLAN NUMBER
T07-08A