

- ① CONCRETE POST BASE DEPTH (TYP.):  
TYPE 3 FENCE = 3'-0"  
TYPE 4 FENCE = 2'-0"
- ② GATE POST (TYP.) ~ 3 1/2" (IN.) DIAM.  
(NOM. SCH. 40)
- ③ TOP HINGE ~ 180° SWING (TYP.)
- ④ BOTTOM HINGE ~ 180° SWING (TYP.)
- ⑤ TRUSS ROD (TYP.)
- ⑥ TIE WIRES (TYP.) ~ SPACED AT 14" (IN.) MAX.
- ⑦ TOP RAIL (TYP.)
- ⑧ HOG RINGS ~ SPACED AT 24" (IN.) MAX. (TYP.)
- ⑨ TENSION WIRES (TYP.)
- ⑩ FABRIC BAND (TYP.)
- ⑪ STRETCHER BAR (TYP.)
- ⑫ PULL POST

- ⑬ CHAIN LINK FENCE FABRIC (TYP.)
- ⑭ MATCH FENCE SELVAGE (TYP.)
- ⑮ TENSION WIRE ALONG BOTTOM OF FENCE  
(TYPE 3 FENCE ONLY) (TYP.)


**NOTES:**

1. MATERIALS SHALL MEET THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS 9-16.
2. ALL FENCE MATERIAL SHALL BE BLACK VINYL COATED.
3. SEE **CHAIN LINK GATE BLOW-UP DETAILS ON SHEET T07-08C.**

REV. NO.	DATE	BY	APPROVED
1	5/16	RAW	MHA
2	9/21	RAW	MHA

PUBLIC WORKS - STREETS AND TRANSPORTATION

APPROVED BY: *M. H. ...*  
ENGINEER MANAGER  
APPROVED DATE: 9/1/2021



CHAIN LINK DOUBLE GATE  
TYPES 3 AND 4  
STANDARD PLAN NUMBER  
T07-08B