



ASHTO SOIL TYPE	ASPHALT THICKNESS	BASE ROCK THICKNESS
A-1 TO A-5	0.40'	0.85'
A-6	0.45'	1.00'
A-7	NO SECTION ESTIMATED	NO SECTION ESTIMATED
OTHER	NO SECTION ESTIMATED	NO SECTION ESTIMATED

NOTES:

1. SEE STANDARD PLAN T10-00 FOR GENERAL NOTES.
2. WIDER SIDEWALKS MAY BE REQUIRED UNDER SPECIAL CIRCUMSTANCES.
3. ADDITIONAL TRAFFIC CALMING MAY BE REQUIRED. COORDINATE WITH THE CITY.
4. BICYCLE STENCIL PAVEMENT MARKING (SHARROW) IS REQUIRED FOR ALL SHARED ROADWAY SEGMENTS. SEE STANDARD PLAN T29-61.
5. CENTER LINE STRIPING SHOULD NOT BE USED.
6. STORMWATER MANAGEMENT TO BE INCORPORATED. COORDINATE WITH THE CITY.
7. ALL NEIGHBORHOOD CIRCULATORS REQUIRE STREET LIGHTING, SEE STANDARD PLAN T08-31.
8. DIAGONAL PARKING IS BACK IN ONLY.

REV NO.	DATE	BY	APPR
1	9/21	RAW	MHA

PUBLIC WORKS – STREETS AND TRANSPORTATION

APPROVED BY: *M.H. Pedraza*
ENGINEER MANAGER

APPROVED DATE: 9/1/2021



HEIGHTS DISTRICT
REDEVELOPMENT INTERNAL
STREET ANGLED PARKING

STANDARD PLAN NUMBER
T08-13