



| AASHTO SOIL TYPE | ASPHALT THICKNESS    | BASE ROCK THICKNESS  |
|------------------|----------------------|----------------------|
| A-1 TO A-5       | 0.85'                | 0.85'                |
| A-6              | 0.90'                | 1.25'                |
| A-7              | NO SECTION ESTIMATED | NO SECTION ESTIMATED |
| OTHER            | NO SECTION ESTIMATED | NO SECTION ESTIMATED |

**NOTES:**

1. MEANDERING SIDEWALKS MAY BE ALLOWED WITH THE DIRECTOR'S APPROVAL.
  2. WIDER SIDEWALKS MAY BE REQUIRED UNDER SPECIAL CIRCUMSTANCES.
  3. SEE STANDARD PLAN T10-00 FOR GENERAL NOTES.
- \* TRAVEL LANE MAY BE REDUCED TO 11' MINIMUM TO ACCOMMODATE 6' BIKE LANE WHEN CURB AND GUTTER (A-1) IS USED.

| REV NO. | DATE | BY  | APPR |
|---------|------|-----|------|
| 1       | 7/14 | RAW | MHA  |
| 2       | 3/16 | RAW | MHA  |
| 3       | 3/17 | RAW | MHA  |
| 4       | 7/19 | RAW | MHA  |
| 5       | 2/21 | OIS | MHA  |
| 6       | 9/21 | RAW | MHA  |

PUBLIC WORKS - STREETS AND TRANSPORTATION

APPROVED BY: *M.H. Pedraza*  
ENGINEER MANAGER

APPROVED DATE: 9/1/2021



4-LANE PRINCIPAL ARTERIAL WITH CENTER LEFT-TURN LANE AND BIKE LANES

|                      |        |
|----------------------|--------|
| STANDARD PLAN NUMBER | T10-06 |
|----------------------|--------|