



AASHTO SOIL TYPE	ASPHALT THICKNESS	BASE ROCK THICKNESS
A-1 TO A-5	0.75'	0.85'
A-6	0.80'	1.25'
A-7	NO SECTION ESTIMATED	
OTHER	NO SECTION ESTIMATED	

**NOTES:**

1. MEANDERING SIDEWALKS MAY BE ALLOWED WITH THE DIRECTOR'S APPROVAL.
  2. WIDER SIDEWALKS MAY BE REQUIRED UNDER SPECIAL CIRCUMSTANCES.
  3. SEE STANDARD PLAN T10-00 FOR GENERAL NOTES.
- \* TRAVEL LANE MAY BE REDUCED TO 11' MINIMUM TO ACCOMMODATE 6' BIKE LANE WHEN CURB AND GUTTER (A-1) IS USED.

REV. NO.	DATE	BY	APPR
1	7/14	RAW	MHA
2	3/16	RAW	MHA
3	3/17	RAW	MHA
4	7/19	RAW	MHA
5	2/21	OIS	MHA
6	9/21	RAW	MHA

PUBLIC WORKS - STREETS AND TRANSPORTATION

APPROVED BY: *M.H. Pedulla*  
ENGINEER MANAGER

APPROVED DATE: 9/1/2021



4-LANE MINOR ARTERIAL WITH BIKE LANES

STANDARD PLAN NUMBER  
T10-10