



AASHTO SOIL TYPE	ASPHALT THICKNESS	BASE ROCK THICKNESS
A-1 TO A-5	0.40'	0.75'
A-6	0.40'	0.85'
A-7	0.45'	1.25'
OTHER	NO SECTION ESTIMATED	

NOTES:

1. WIDER SIDEWALKS MAY BE REQUIRED UNDER SPECIAL CIRCUMSTANCES.
2. PARKING/BULB OUT RESTRICTED TO ONE SIDE ONLY.
3. SEE **STREET TERMINATION DETAIL T10-01** FOR ADDITIONAL CUL-DE-SAC REQUIREMENTS.
4. SEE **NARROW LOT STREET PLAN DETAIL T10-24A** FOR ADDITIONAL INFORMATION.
5. SEE STANDARD PLAN T10-00 FOR GENERAL NOTES.

REV NO.	DATE	BY	APPR	PUBLIC WORKS - STREETS AND TRANSPORTATION
1	8/08	RAW	MHA	
2	7/14	RAW	MHA	
3	3/17	RAW	MHA	
4	7/19	RAW	MHA	
5	2/21	OIS	MHA	
6	9/21	RAW	MHA	

APPROVED BY: *M.H. Sedalla*
ENGINEER MANAGER
APPROVED DATE: 9/1/2021



NARROW LOT STREET SECTION	STANDARD PLAN NUMBER T10-24B
---------------------------	---------------------------------

FOR NARROW LOT DESIGN PROJECTS ONLY