



**NOTES:**

- ① INSTALL PEDESTRIAN SIGNAL AT ORIENTATION PER PLANS WITH TYPE E MOUNT ON SIDE OF POLE. SEE T20-09D AND WSDOT STANDARD PLAN J-75.10-xx.
- ② SEE **TYPE II AND TYPE III TRAFFIC SIGNAL POLE FOUNDATION DETAIL T20-15** AND SPECIFICATIONS.
- ③ PROVIDE COVERED 5" X 7" HAND HOLE AT 180° FROM MAST ARM (TYP.).
- ④ PROVIDE COVERED 5" X 7" HAND HOLE AT 180° FROM ARM.
- ⑤ INSTALL **ADA PEDESTRIAN AUDIBLE PUSH BUTTON ASSEMBLY** SEE **DETAIL T20-09B** (UNLESS SPECIFIED OTHERWISE) WITH ARROW POINTING TOWARDS CROSSWALK. SEE PLANS FOR ORIENTATION.
- ⑥ INSTALL SIGNAL ON SIDE OF POLE WITH TYPE K MOUNTING, SEE WSDOT STANDARD PLAN J-75.10-xx.
- ⑦ TOP OF POLE SHALL BE COVERED.
- ⑧ STANDARD SAFETY LIGHT MAST ARM. ALTERNATE ARMS 1 AND 2 ARE WSDOT STANDARDS TO BE USED ONLY IN SPECIAL CASES. LOCATE ARM AT 0° ABOVE MAST ARM, EXCEPT AS INDICATED ON POLE SCHEDULE AND SIGNAL PLANS.
- ⑨ INSTALL LUMINAIRE. (SEE **POLE SCHEDULE** FOR FIXTURE DETAILS).
- ⑩ INSTALL RECESSED TERMINAL COMPARTMENT (SEE **DETAIL T20-03**) 225" FROM ARM UNLESS OTHERWISE SPECIFIED. **ALL WIRING TO POLE FROM CONTROLLER CABINET SHALL TERMINATE IN THE COMPARTMENT.**
- ⑪ FIXTURE MOUNTING HEIGHT K SHALL BE 30' OR AS SPECIFIED IN POLE SCHEDULE.
- ⑫ CLAM SHELL BASE DECORATIVE COVER REQUIRED ON TYPE II D, TYPE III D, TYPE II DT AND TYPE III DT STANDARDS.

I:\CITYPPS\AUTOCAD\STD\_DETAILS\DRAWING\_FILES\T20-02

REV NO.	DATE	BY	APPR	PUBLIC WORKS - STREETS AND TRANSPORTATION
1	8/08	RAW	CJC	
2	7/14	RAW	CJC	
3	1/15	RAW	CJC	
4	7/18	RAW	CJC	
5	7/19	RAW	CJC	
6	9/21	RAW	CJC	

APPROVED BY: *[Signature]*  
 TRAFFIC ENGINEER MANAGER  
 APPROVED DATE: 9/1/2021



POLE CONFIGURATION FOR  
 TYPE II, TYPE III, TYPE B AND TYPE S  
 TRAFFIC SIGNAL STANDARDS

STANDARD PLAN NUMBER  
 T20-02