



FIXTURE MOUNTING HEIGHT (FT.), "K"	POLE HEIGHT (FT.)	USE
20	18	
25	23	RESIDENTIAL
30	28	ARTERIAL
35	33	

ARM LENGTH (FT.) "J"	ARM RISE (INCHES)
4	32
6 (STD.)	32
8	32
10	32
12	32

TAPERED SHAFT AND ARM SHALL BE SINGLE MEMBERS. TYPE A OR AT STANDARD SHALL BE A TAPERED SPUN. SHAFT SHALL BE HIGH GLOSS COLOR. SEE APPROVED MATERIALS LIST POLE OPTIONS.

MIN. WALL THICKNESS OF 0.188"

POLE HEIGHT  
FIXTURE MOUNTING HEIGHT "K"

**NOTES:**

1. THIS LIGHTING STANDARD CAN BE USED ALONG RESIDENTIAL AND LOCAL ACCESS STREETS.
2. CHECK AND COORDINATE WITH CLARK PUBLIC UTILITIES (CPU) FOR ANY HEIGHT CLEARANCE CONFLICTS.

APPROVED MATERIALS LIST:  
SEE CITY OF VANCOUVER'S WEB SITE;  
<http://www.cityofvancouver.us/publicworks/page/transportation-development-review-information>

HANDHOLE WITH NOMINAL SIZE OF 3"x6" OR LARGER

2' MIN. TO FACE OF CURB  
7' MIN. TO EDGE OF PAVEMENT  
SEE T21-16 LIGHTING STANDARD POSITION OPTIONS

PRECAST CONCRETE FOUNDATION BASE, SEE DETAIL T21-11A OR CAST-IN-PLACE CONCRETE FOUNDATION T21-11B OR WSDOT STANDARD PLAN J-28.30-xx

I:\CITYPPS\AUTOCAD\STD\_DETAILS\DRAWING\_FILES\T21-02

REV NO.	DATE	BY	APPR	AGE
1	4/06	RAW		AGE
2	2/07	RAW		AGE
3	8/08	RAW		AGE
4	1/15	RAW		AGE
5	7/19	RAW	CJC	
6	9/21	RAW	CJC	

PUBLIC WORKS - STREETS AND TRANSPORTATION

APPROVED BY: *[Signature]*  
TRAFFIC ENGINEER MANAGER

APPROVED DATE: 9/1/2021



TYPE A AND TYPE AT LIGHTING STANDARDS

STANDARD PLAN NUMBER  
T21-02