

NOTES:

1. DIRECT BURIAL POLES ARE AN OPTION FOR TYPE D LIGHTING STANDARDS, SEE MATERIALS LIST.

APPROVED MATERIALS LIST:

SEE CITY OF VANCOUVER'S WEB SITE;

<http://www.cityofvancouver.us/publicworks/page/transportation-development-review-information>

NOTE:

DIFFERENT MANUFACTURER PARTS CAN NOT BE INTERCHANGED.

DECORATIVE SPUN ALUMINUM RING WITH SLOTS AND ESCUTCHEONS. SLOTS ALLOW LIGHT TO HIGHLIGHT RING

HID LIGHTING AVAILABLE - HPS, LPS, MV, MH VARIOUS REFLECTOR SYSTEMS AVAILABLE FOR TYPE; III, IV, V DISTRIBUTIONS

REMOVABLE DOOR FOR EASY ACCESS TO WIRING

PROVIDE 110 VAC RECEPTACLE

TAPERED SHAFT AND ARM SHALL BE SINGLE MEMBERS. TYPE D STANDARD SHALL BE A FLUTED, TAPERED, COMPOSITE FIBERGLASS REINFORCED SHAFT (OR ALUMINUM)

DECORATIVE COLLAR TYPE "L"

BASE ATTACHED WITH STAINLESS STEEL HEX LOCKING SCREWS

ACCESS DOOR WITH TAMPER-RESISTANT SCREW IN BASE, ALIGN WITH HAND HOLE IN POLE

BRASS FINAL

M=20' (MAX.)

2' MIN. TO FACE OF CURB

SEE T21-16
LIGHTING
STANDARD
POSITION
OPTIONS

FOUNDATION, SEE DETAIL T21-11B
OR WSDOT STANDARD PLAN
J-28.30-xx

REFERENCES TO WSDOT STANDARD PLANS, USE THE MOST CURRENT VERSION OF THESE STANDARD PLANS.

NOTE:

THIS LIGHTING STANDARD SHALL BE USED IN THE UPTOWN LIGHTING DISTRICT AND ON RESIDENTIAL STREETS, UNLESS THE SURROUNDING NEIGHBORHOOD LIGHTING FIXTURE IS THE TYPE A, TYPE AT OR TYPE N AND WILL BE DETERMINED ON A CASE BY CASE BASIS.

REV NO.	DATE	BY	APPR	DESCRIPTION
2	2/07	RAW	AGE	
3	8/08	RAW	AGE	
4	7/14	RAW	CJC	
5	1/15	RAW	CJC	
6	9/21	RAW	CJC	
7		CDC	CJC	

PUBLIC WORKS - STREETS AND TRANSPORTATION

APPROVED BY: _____
TRAFFIC ENGINEER MANAGER

APPROVED DATE: _____

CITY OF
Vancouver
WASHINGTON

TYPE D
LIGHTING STANDARDS

STANDARD PLAN
NUMBER

T21-04