

**NOTES:**

1. DIRECT BURIAL POLES ARE AN OPTION FOR TYPE D LIGHTING STANDARDS, SEE MATERIALS LIST.

**APPROVED MATERIALS LIST:**

SEE CITY OF VANCOUVER'S WEB SITE;  
<http://www.cityofvancouver.us/publicworks/page/transportation-development-review-information>

DECORATIVE SPUN ALUMINUM RING WITH SLOTS AND ESCUTCHEONS. SLOTS ALLOW LIGHT TO HIGHLIGHT RING

BRASS FINAL

HID LIGHTING AVAILABLE - HPS, LPS, MV, MH VARIOUS REFLECTOR SYSTEMS AVAILABLE FOR TYPE; III, IV, V DISTRIBUTIONS

REMOVABLE DOOR FOR EASY ACCESS TO WIRING

PROVIDE 110 VAC RECEPTACLE

TAPERED SHAFT AND ARM SHALL BE SINGLE MEMBERS. TYPE D STANDARD SHALL BE A FLUTED, TAPERED, COMPOSITE FIBERGLASS REINFORCED SHAFT (OR ALUMINUM)

M=20' (MAX.)

DECORATIVE COLLAR TYPE "L"

2' MIN. TO FACE OF CURB

SEE T21-16 LIGHTING STANDARD POSITION OPTIONS

BASE ATTACHED WITH STAINLESS STEEL HEX LOCKING SCREWS

ACCESS DOOR WITH TAMPER-RESISTANT SCREW IN BASE, ALIGN WITH HAND HOLE IN POLE

PRECAST CONCRETE FOUNDATION BASE, SEE DETAIL T21-11A OR CAST-IN-PLACE CONCRETE FOUNDATION T21-11B OR WSDOT STANDARD PLAN J-28.30-xx

**NOTE:**

DIFFERENT MANUFACTURER PARTS CAN NOT BE INTERCHANGED.

REFERENCES TO WSDOT STANDARD PLANS, USE THE MOST CURRENT VERSION OF THESE STANDARD PLANS.

**NOTE:**

THIS LIGHTING STANDARD SHALL BE USED IN THE UPTOWN LIGHTING DISTRICT AND ON RESIDENTIAL STREETS, UNLESS THE SURROUNDING NEIGHBORHOOD LIGHTING FIXTURE IS THE TYPE A, TYPE AT OR TYPE N AND WILL BE DETERMINED ON A CASE BY CASE BASIS.

I:\CITYPPS\AUTOCAD\STD\_DETAILS\DRAWING\_FILES\T21-04

REV. NO.	DATE	BY	APPR	AGE
1	4/06	RAW	AGE	
2	2/07	RAW	AGE	
3	8/08	RAW	AGE	
4	7/14	RAW	CJC	
5	1/15	RAW	CJC	
6	9/21	RAW	CJC	

PUBLIC WORKS - STREETS AND TRANSPORTATION

APPROVED BY: *[Signature]*  
 TRAFFIC ENGINEER MANAGER

APPROVED DATE: 9/1/2021



TYPE D  
 LIGHTING STANDARDS

STANDARD PLAN NUMBER  
 T21-04