


**NOTE:**

- ① PVC INTERCONNECT CONDUIT WITH DETECTABLE MULE TAPE. (SEE PLANS AND SPECIFICATIONS).
- ② SEE STANDARD PLAN T20-38E AND STANDARD SPECIFICATIONS FOR FOUNDATION AND PAD DEPTH AND SIZE.
- ③ SEE STANDARD SPECIFICATIONS FOR DEPTH.
- ④ LOCATE SERVICE PEDESTAL SIDE ADJACENT TO CONTROLLER CABINET OR MOVE MORE THAN 20' AWAY. HANDLES SHALL POINT OUTWARD. METER OPENING SHALL FACE STREET.
- ⑤ MOUNTING BOLTS INSIDE CABINET. NUTS, BOLTS AND SCREWS WILL NOT BE VISIBLE FROM OUTSIDE OF ENCLOSURE.
- ⑥ SERVICE CABINET DOOR.

I:\CITYPPS\AUTOCAD\STD\_DETAILS\DRAWING\_FILES\T22-01

REV. NO.	DATE	BY	APPR	PUBLIC WORKS - STREETS AND TRANSPORTATION
1	3/06	RAW	AGE	 APPROVED BY: TRAFFIC ENGINEER MANAGER APPROVED DATE: 9/1/2021
2	2/07	RAW	AGE	
3	8/08	RAW	AGE	
4	7/14	RAW	CJC	
5	4/18	RAW	CJC	
6	9/21	RAW	CJC	



TYPICAL INTERCONNECT CONDUIT AND CABLE INSTALLATION

STANDARD PLAN NUMBER  
T22-01