



**NOTE:**

1. SPEED BUMP SHALL BE CONSTRUCTED OF HOT MIX ASPHALT CLASS 3/8" PG 58H-22 0.3 TO 3.0 ESAL MIX DESIGN UNLESS OTHERWISE SPECIFIED.

**SIGNS:**

- ① INSTALL MUTCD STANDARD W17-1 ("SPEED BUMP") SIGN 150' (POSTED SPEED=25MPH) OR 175' (POSTED SPEED=30MPH) AHEAD OF RAISED CROSSWALK AT BEGINNING OF A SERIES OF HUMPS OR AS NECESSARY. SEE SIGN MOUNTING DETAILS T29-02 AND T29-03.
- ② IN PLACING SIGNS AT MULTIPLE SPEED BUMPS ALONG A ROADWAY, HAVE THE SIGNS AT THE BEGINNING OF THE INSTALLATION WITH SUPPLEMENTAL SIGN "W16-4" DESIGNATING HOW MANY BLOCKS OR MILEAGE, NOT AT EACH RAISED CROSSWALK.

I:\CITYAPPS\AUTOCAD\STD\_DETAILS\DRAWING\_FILES\T02-22.DWG



<b>SPEED BUMP</b>			STD. PLAN NO. <b>T02-22</b>
CITY OF VANCOUVER DEPARTMENT OF PUBLIC WORKS TRANSPORTATION DIVISION			
DRAWN BY CDC	APPROVED BY <i>M.H.H.</i>	APPROVAL DATE 8/04	
REVISION 7	APPROVED BY <i>M.H.H.</i>	APPROVAL DATE 3/24	