



- ① PREFERRED TWO-WAY DRIVE OPPOSITE MEDIAN OPENINGS.
- ② PREFERRED TWO WAY DRIVE FOR INDUSTRIAL USES ON HIGH VOLUME STREETS.
- ③ RAISED MEDIAN SET BACK FROM STREET TO ALLOW PEDESTRIAN TRAFFIC.

NOTES:

1. MINIMUM DRIVE LENGTH IS 20 FEET, MEASURED FROM THE BACK OF SIDEWALK TO THE ENTRANCE OF THE OFF STREET PARKING AREA.
2. DIMENSIONS MAY VARY WITH ANALYSIS OF THE TURNING MOVEMENTS OF THE TYPICAL VEHICLE.

I:\CITYAPPS\AUTOCAD\STD_DETAILS\DRAWING_FILES\T04-09.DWG



COMMERCIAL / HIGH VOLUME TWO-WAY DRIVEWAYS			STD. PLAN NO. T04-09
CITY OF VANCOUVER DEPARTMENT OF PUBLIC WORKS TRANSPORTATION DIVISION			
DRAWN BY CDC	APPROVED BY <i>M.H.H.</i>	APPROVAL DATE 8/04	
REVISION 7	APPROVED BY <i>M.H.H.</i>	APPROVAL DATE 3/24	