



- ① CONCRETE POST BASE DEPTH (TYP.):
TYPE 3 FENCE = 3'-0"
TYPE 4 FENCE = 2'-0"
- ② GATE POST (TYP.) ~ 3 1/2" (IN.) DIAM.
(NOM. SCH. 40)
- ③ TOP HINGE ~ 90° SWING (TYP.)
- ④ BOTTOM HINGE ~ 90° SWING (TYP.)
- ⑤ TRUSS ROD (TYP.)
- ⑥ TIE WIRES (TYP.) ~ SPACED AT 14" (IN.) MAX.
- ⑦ TOP RAIL (TYP.)
- ⑧ HOG RINGS ~ SPACED AT 24" (IN.) MAX. (TYP.)
- ⑨ TENSION WIRES (TYP.)
- ⑩ FABRIC BAND (TYP.)
- ⑪ STRETCHER BAR (TYP.)
- ⑫ PULL POST

- ⑬ CHAIN LINK FENCE FABRIC (TYP.)
- ⑭ MATCH FENCE SELVAGE (TYP.)
- ⑮ TENSION WIRE ALONG BOTTOM OF FENCE
(TYPE 3 FENCE ONLY) (TYP.)
- ⑯ TENSION WIRE FOR GATE POST ~
REQUIRED ONLY ON HINGE SIDE

NOTES:

- 1. MATERIALS SHALL MEET THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS 9-16.
- 2. ALL FENCE MATERIAL SHALL BE BLACK VINYL COATED.



CHAIN LINK SINGLE GATE TYPES 3 AND 4

CITY OF VANCOUVER
DEPARTMENT OF PUBLIC WORKS
TRANSPORTATION DIVISION

DRAWN BY	APPROVED BY	APPROVAL DATE
CDC	MHH	3/16
REVISION	APPROVED BY	APPROVAL DATE
3	MHH	3/24

STD. PLAN NO.

T07-08A