



- ① CONCRETE POST BASE DEPTH (TYP.):
TYPE 3 FENCE = 3'-0"
TYPE 4 FENCE = 2'-0"
- ② GATE POST (TYP.) ~ 3 1/2" (IN.) DIAM.
(NOM. SCH. 40)
- ③ TOP HINGE ~ 180° SWING (TYP.)
- ④ BOTTOM HINGE ~ 180° SWING (TYP.)
- ⑤ TRUSS ROD (TYP.)
- ⑥ TIE WIRES (TYP.) ~ SPACED AT 14" (IN.) MAX.
- ⑦ TOP RAIL (TYP.)
- ⑧ HOG RINGS ~ SPACED AT 24" (IN.) MAX. (TYP.)
- ⑨ TENSION WIRES (TYP.)
- ⑩ FABRIC BAND (TYP.)
- ⑪ STRETCHER BAR (TYP.)
- ⑫ PULL POST

⑬ CHAIN LINK FENCE FABRIC (TYP.)

⑭ MATCH FENCE SELVAGE (TYP.)

⑮ TENSION WIRE ALONG BOTTOM OF FENCE
(TYPE 3 FENCE ONLY) (TYP.)

NOTES:

1. MATERIALS SHALL MEET THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS 9-16.
2. ALL FENCE MATERIAL SHALL BE BLACK VINYL COATED.
3. SEE CHAIN LINK GATE BLOW-UP DETAILS ON SHEET T07-08C.



CITY OF VANCOUVER
DEPARTMENT OF PUBLIC WORKS
TRANSPORTATION DIVISION

DRAWN BY		APPROVED BY		APPROVAL DATE	
CDC		MHH		3/16	
REVISION		APPROVED BY		APPROVAL DATE	
3		MHH		3/24	

STD. PLAN NO.
T07-08B

CHAIN LINK DOUBLE GATE TYPES 3 AND 4