

CURB TO CURB

*FIRE CODE MAY REQUIRE 20'.

NOTES:

- PRIOR TO ANY PAVEMENT DESIGN, CONTACT PUBLIC WORKS PAVEMENT MANAGER FOR DESIGN METHODOLOGY.
- CROWN MAY BE ELIMINATED BY SLOPING IN ONE DIRECTION. INVERTED SECTION REQUIRES A ROAD MODIFICATION. 'n
- FOR INFILL STREETS, REFER TO V.M.C. 11.80.060 INFILL DEVELOPMENT TRAFFIC STANDARDS. 3
- PROVIDE TURNAROUNDS PER STREET TERMINATION DETAIL T10-01 AND VMC TABLE 11.80.070.C-3. 4
- PERVIOUS CONCRETE MAY BE USED ON THE TRAVEL SURFACE OF A PRIVATE STREET ON A CASE BY CASE BASIS WITH THE APPROVAL OF CITY OF VANCOUVER TRANSPORTATION DEVELOPMENT REVIEW. THE PERVIOUS CONCRETE DESIGN SHALL BE INCLUDED WITH THE PROJECT'S FC SUBMITTAL. S.
- 6. SEE STANDARD PLAN T10-00 FOR GENERAL NOTES.



PRIVATE STREET 1-4 DWELLINGS

CITY OF VANCOUVER
DEPARTMENT OF PUBLIC WORKS
TRANSPORTATION DIVISION

DRAWN BY	APPROVED BY	APPROVAL DATE
CDC	MHH	8/04
REVISION	APPROVED BY	APPROVAL DATE
7	MAHA	3/24

STD. PLAN NO. T10-18