



**NOTES:**

- ① SEE TYPE PS, TYPE I AND TYPE PPB TRAFFIC SIGNAL POLE FOUNDATION STANDARD PLAN T20-16 AND SPECIFICATIONS FOR FOUNDATION INFORMATION.
- ② 8' GROUND ROD - CONNECT TO BASE.
- ③ TYPE I STANDARD (12'-6" IN LENGTH).
- ④ 1-WAY, 1-SECTION, 12" YELLOW LED MOUNTED ABOVE SIGN..
- ⑤ TUNNEL VISOR.
- ⑥ LOCKNIPPLE, 1 1/2" DIA. WITH GASKET, WASHER AND CONDUIT LOCKNUT.
- ⑦ SERRATED OR FLANGED ELBOW.
- ⑧ CONDUIT NIPPLE, 1 1/2" DIA.
- ⑨ TOP MOUNT SEE WSDOT DETAIL J-21.16.xx AND J-21.17.xx. IF SIGN IS MOUNTED ON LIGHT POLE USE MODIFIED TYPE K MOUNT.
- ⑩ SLIPFITTER.
- ⑪ ALUMINUM CASING.
- ⑫ END CAP.
- ⑬ MOUNTING BRACKET.

I:\CITYAPPS\AUTOCAD\STD\_DETAILS\DRAWING\_FILES\T20-14.DWG



**SIGN AND FLASHER ASSEMBLY**

CITY OF VANCOUVER  
DEPARTMENT OF PUBLIC WORKS  
TRANSPORTATION DIVISION

DRAWN BY	APPROVED BY	APPROVAL DATE
CDC	<i>[Signature]</i>	8/04
REVISION	APPROVED BY	APPROVAL DATE
7	<i>[Signature]</i>	3/24

STD. PLAN NO.  
**T20-14**