

NOTES:

1. DIRECT BURIAL POLES ARE AN OPTION FOR TYPE D LIGHTING STANDARDS, SEE MATERIALS LIST.

APPROVED MATERIALS LIST:

SEE CITY OF VANCOUVER'S WEB SITE;

<http://www.cityofvancouver.us/publicworks/page/transportation-development-review-information>

DECORATIVE SPUN ALUMINUM RING WITH SLOTS AND ESCUTCHEONS. SLOTS ALLOW LIGHT TO HIGHLIGHT RING

BRASS FINAL

HID LIGHTING AVAILABLE - HPS, LPS, MV, MH VARIOUS REFLECTOR SYSTEMS AVAILABLE FOR TYPE; III, IV, V DISTRIBUTIONS

REMOVABLE DOOR FOR EASY ACCESS TO WIRING

PROVIDE 110 VAC RECEPTACLE

TAPERED SHAFT AND ARM SHALL BE SINGLE MEMBERS. TYPE D STANDARD SHALL BE A FLUTED, TAPERED, COMPOSITE FIBERGLASS REINFORCED SHAFT (OR ALUMINUM)

NOTE:

DIFFERENT MANUFACTURER PARTS CAN NOT BE INTERCHANGED.

M=20' (MAX.)

DECORATIVE COLLAR TYPE "L"

2' MIN. TO FACE OF CURB

SEE T21-16 LIGHTING STANDARD POSITION OPTIONS

BASE ATTACHED WITH STAINLESS STEEL HEX LOCKING SCREWS

ACCESS DOOR WITH TAMPER-RESISTANT SCREW IN BASE, ALIGN WITH HAND HOLE IN POLE

FOUNDATION, SEE DETAIL T21-11B OR WSDOT STANDARD PLAN J-28.30-xx

NOTE:

THIS LIGHTING STANDARD SHALL BE USED IN THE UPTOWN LIGHTING DISTRICT AND ON RESIDENTIAL STREETS, UNLESS THE SURROUNDING NEIGHBORHOOD LIGHTING FIXTURE IS THE TYPE A, TYPE AT OR TYPE N AND WILL BE DETERMINED ON A CASE BY CASE BASIS.

REFERENCES TO WSDOT STANDARD PLANS, USE THE MOST CURRENT VERSION OF THESE STANDARD PLANS.

TYPE "D" LIGHTING STANDARDS



CITY OF VANCOUVER
DEPARTMENT OF PUBLIC WORKS
TRANSPORTATION DIVISION

| DRAWN BY | APPROVED BY | APPROVAL DATE |
|----------|-------------|---------------|
| CDC | | 8/04 |
| REVISION | APPROVED BY | APPROVAL DATE |
| 7 | | 3/24 |

STD. PLAN NO.
T21-04